

# Ecodesign directive

EUROPEAN COMMISSION REGULATIONS (EU) No 1253/2014



PARTNER  
IN VENTILATION  
2VV.CZ

a) suppliers name or trade mark	2VV s.r.o.															
b)	c)	d)	f)	g)	h)	i)	j)	k)	l)	n)	o)		p)	q)	r)	
supplier's model identifier	ErP - Conformity (2016/2019/2020)	ErP - Typology (RVU or NRVU)	ErP - Multi-speed drive or variable speed drive	ErP - Thermal efficiency (%)	ErP - nominal air flow (m <sup>3</sup> /s)	ErP - Effective electric power (kW)	ErP - SFPint (W/(m <sup>3</sup> /s))	ErP - face velocity at the nominal airflow (m/s)	ErP - nominal external pressure (Pa)	ErP - Internal pressure drop of the components (Pa)	ErP - Static efficiency of fans (%)	ErP - maximum external leakage (%)	ErP - maximum internal leakage (%)	ErP - Energy classification of the filters	ErP - Description of the visual filter warning for the NRVU with filters	ErP - Casing sound power level (LwA(dB))
HR953-150U CBE75-XS0	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-XE1	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-XV1	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-XVC	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-XD3	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-ES0	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-EE1	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-EV1	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-EVC	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-ED3	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-220U CBE75-XS0	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-XE1	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-XV1	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-XVC	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-XD3	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-ES0	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-EE1	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-EV1	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-EVC	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-ED3	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
s) internet address	<a href="https://www.2vv.cz/en/products/">https://www.2vv.cz/en/products/</a>															

a) suppliers name or trade mark	2VV s.r.o.															
b)	c)	d)	f)	g)	h)	i)	j)	k)	l)	n)	o)		p)	q)	r)	
supplier's model identifier	ErP - Conformity (2016/2018/2020)	ErP - Typology (RVU or NRVU)	ErP - Multi-speed drive or variable speed drive	ErP - Thermal efficiency (%)	ErP - nominal air flow (m <sup>3</sup> /s)	ErP - Effective electric power (kW)	ErP - SFPint (W/(m <sup>3</sup> /s))	ErP - face velocity at the nominal airflow (m/s)	ErP - nominal external pressure (Pa)	ErP - Internal pressure drop of the components (Pa)	ErP -Static efficiency of fans (%)	ErP - maximum external leakage (%)	ErP - maximum internal leakage (%)	ErP - Energy classification of the filters	ErP - Description of the visual filter warning for the NRVU with filters	ErP - Casing sound power level (LWA(dB))
HR953-320U CBE75-XS0	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-XE1	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-XV1	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-XVC	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-XD3	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-ES0	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-EE1	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-EV1	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-EVC	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-ED3	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-470U CBE75-XS0	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-XE1	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-XV1	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-XVC	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-XD3	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-ES0	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-EE1	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-EV1	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-EVC	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-ED3	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
s) internet address	<a href="https://www.2vv.cz/en/products/">https://www.2vv.cz/en/products/</a>															

a) suppliers name or trade mark		2VV s.r.o.														
b)		c)	d)	f)	g)	h)	i)	j)	k)	l)	n)	o)		p)	q)	r)
supplier's model identifier	ErP - Conformity (2016/2018/2020)	ErP - Typology (RVU or NRVU)	ErP - Multi-speed drive or variable speed drive	ErP - Thermal efficiency (%)	ErP - nominal air flow (m <sup>3</sup> /s)	ErP - Effective electric power (kW)	ErP - SFPint (W/(m <sup>3</sup> /s))	ErP - face velocity at the nominal airflow (m/s)	ErP - nominal external pressure (Pa)	ErP - Internal pressure drop of the components (Pa)	ErP -Static efficiency of fans (%)	ErP - maximum external leakage (%)	ErP - maximum internal leakage (%)	ErP - Energy classification of the filters	ErP - Description of the visual filter warning for the NRVU with filters	ErP - Casing sound power level (LWA(dB))
HR953-150U EBE75-XS0	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-XE1	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-XV1	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-XVC	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-XD3	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-ES0	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-EE1	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-EV1	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-EVC	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-ED3	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-220U EBE75-XS0	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-XE1	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-XV1	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-XVC	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-XD3	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-ES0	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-EE1	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-EV1	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-EVC	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-ED3	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
<b>s) internet address</b>	<a href="https://www.2vv.cz/en/products/">https://www.2vv.cz/en/products/</a>															

a) suppliers name or trade mark	2VV s.r.o.															
b)	c)	d)	f)	g)	h)	i)	j)	k)	l)	n)	o)		p)	q)	r)	
supplier's model identifier	ErP - Conformity (2016/2018/2020)	ErP - Typology (RVU or NRVU)	ErP - Multi-speed drive or variable speed drive	ErP - Thermal efficiency (%)	ErP - nominal air flow (m <sup>3</sup> /s)	ErP - Effective electric power (kW)	ErP - SFPint (W/(m <sup>3</sup> /s))	ErP - face velocity at the nominal airflow (m/s)	ErP - nominal external pressure (Pa)	ErP - Internal pressure drop of the components (Pa)	ErP -Static efficiency of fans (%)	ErP - maximum external leakage (%)	ErP - maximum internal leakage (%)	ErP - Energy classification of the filters	ErP - Description of the visual filter warning for the NRVU with filters	ErP - Casing sound power level (LWA(dB))
HR953-320U EBE75-XS0	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-XE1	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-XV1	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-XVC	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-XD3	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-ES0	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-EE1	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-EV1	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-EVC	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-ED3	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-470U EBE75-XS0	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-XE1	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-XV1	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-XVC	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-XD3	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-ES0	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-EE1	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-EV1	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-EVC	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-ED3	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
<b>s) internet address</b>	<a href="https://www.2vv.cz/en/products/">https://www.2vv.cz/en/products/</a>															